

Patented Technology

0.6250 Max
[15.88]

Mounting Holes
 $\phi 0.1880 +.010/-0$ [$\phi 4.78$]
 82° "C" Sink For FHCS Heads
 To Be Slightly Below End Cap
 Surface (4X)

Mtg Hole BC=
 Shaft $\phi + 1.140' \pm .010'$
 [28.95mm]

Shaft ϕ

OD=Shaft $\phi + 1.8600' \pm .02'$
 [47.24mm]


ID= Shaft $\phi + .150 \pm .02'$
 [3.81mm]

Fiber ϕ =Shaft $\phi - .060' \pm .010$ [1.52mm $\pm .25$]

Flat Head Screw Mounting

Notes:

- 1: WTGSL-_____-1FH Supplied With 4, 8-32 X 1" FHCS
- 2: WTGSL-_____-2FH Supplied With 4 M4x.7x25mm FHCS
- 3: Contains 6 Rows Of Conductive Micro Fibers
- 4: To be Installed In Conjunction With AEGIS® Colloidal Silver Coating PN CS015

| | | |
|---|----|---|
| THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T. | | |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN: | | |
| MILLIMETERS <input checked="" type="checkbox"/> | | |
| INCHES <input checked="" type="checkbox"/> | | |
| UNTOLERANCED DIMENSIONS | | |
| OVER | TO | TOLERANCE |
| | | |
| | | |
| | | |
| DATE: 12/7/11 | | |
| ENGINEER: J. Richardson | | |
|  ELECTRO STATIC TECHNOLOGY AN ITW COMPANY | | 31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256 PHONE (207)998-5140 FAX (207)998-5143 |
| WTGSL Bearing Protection Ring | | Rev. A |
| WTGSL Solid Template -_FH | | A |